



DIGITAL MULTI-
FUNCTIONAL SYSTEM

CD 1242 | 1252

CD 1242 | 1252

TWO ALL-ROUNDERS REVEAL THEIR DISTINCTIVE SIDE!

Powerful and productive printing, copying and scanning – this is what the CD 1242 and CD 1252 compact multifunctional systems offer in an extremely efficient and reliable manner. When combined with the optional fax function, the result is an end-to-end, versatile communication solution for every medium- to large-sized office environment. And all this is achieved with maximum efficiency and productivity thanks to the intelligent SynControl technology, which ensures optimal process control. Better still, this quality performance can be adapted to suit every organisation. The new and innovative HyPAS technology allows user-specific applications and customisable workflows to be realised. As a result, complex scan applications, for example, can be adapted to suit the user's situation as required and ease of use increases significantly thanks to the large, adjustable colour touch screen.

PAGESETTER AND FRONT-RUNNER ALL IN ONE.

With a speed of 42 and 52 A4 pages and 23 and 26 A3 pages per minute respectively, a warm-up time of just 30 seconds and the first page after 3.9 seconds, efficiency is just one of the outstanding features of the CD 1242 and CD 1252. In addition, up to 100 A4 images can be processed per minute with the optional simultaneous duplex scanning function, which eliminates the need to turn the original, thus guaranteeing maximum performance and minimum original handling. And in order to ensure that both speed and volume stand up to scrutiny, both systems have a paper capacity of up to 4,200 sheets, making it possible to tackle even the most extensive jobs effortlessly. Paper formats of A6R to A3 and paper weights of up to 200 g/m² will make a world of difference in your office.





The CD 1242 and CD 1252 multifunctional systems will win you over just the same when scanning, in colour or b/w, due to their wide range of scanning options – choose from scan to PC, scan to e-mail, scan to FTP, TWAIN scan, WIA scan and even scan to USB, not to mention the subsequent convenient document management with comprehensive document box functions. All of these features are actively supported by a standard memory of 2,048 MB RAM and a hard disk capacity of 160 GB.

A WEALTH OF POWERFUL OPTIONS.

Various intelligent features make for convenient and flexible handling. Be it job reservation, booklet mode or the administration of management codes, a multitude of office documents and applications can be managed with great ease. The optional finisher, with its additional brochure folding module, mailbin tray and hole punch unit, opens up new possibilities for producing professionally finished output.

ADD A FAX TO MAKE A WINNING FORMULA.

With the optional Super G3 fax kit, efficient faxing with automatic redialling and delayed sending is possible. And if you want to simultaneously receive and send faxes, simply install two fax kits. For complete choice, an internet fax kit is also available.



SIMPLY THE BEST.

Today, processes are increasingly being digitised, making data security a must. For this reason, the CD 1242 and CD 1252 state-of-the-art multifunctional systems are also equipped with extensive security functions like standard compression and encryption of PDF files as well as the support of security protocols such as IPsec and SSL. Encryption and hard disk data overwriting is ensured if the optional Data Security Kit is installed.



NOTHING LEFT TO CHANGE:

- Top print and copy speeds of 42/52 A4 or 23/26 A3 pages per minute
- Minimal warm-up time of only 30 seconds, fast 1st page after 3.9 seconds
- Standard network and USB direct printing
- Top scan speeds of max 100 A4 images/minute, scanning in b/w and colour
- Standard duplex
- Customising of individual user applications and programming of user workflows thanks to innovative HyPAS technology
- Extensive standard memory of 2,048 MB RAM + 160 GB hard disk
- Large paper capacity of up to 4,200 sheets
- Numerous, modular upgradeable ancillaries
- Extensive security features

Standard features:

CD 1242/1252 with 2 x 500 sheet universal cassettes, duplex unit and 160 GB hard disk

- ① Original feeder with automatic reverse function for 100 sheets* or original feeder with simultaneous duplex scanning for 100 sheets** or original cover (type E)**
- ② 2 x 500 sheet universal cassettes** or 3,000 sheet large capacity cassette*, or cabinet**
- ③ Job separator for 100 sheets**
- ④ 500 sheet internal finisher**, staples up to 30 sheets, or 1,000 sheet finisher**, staples up to 50 sheets, or 3,000 sheet finisher*, staples up to 50 sheets
- ⑤ Brochure folding module for max 64-page brochures*
- ⑥ Hole punch unit for 2-/4-hole punching**
- ⑦ Multi tray for max 7 x 100 sheets*
- ⑧ Fax system (S)**
- ⑨-⑫ Data Security Kit (E)**, Internet Fax Kit (A)**, Printed Document Guard Kit (A)**, DT-710 original tray



*option

**option, no illustration

TECHNICAL DATA



	GENERAL
Type	Desktop
Function	Copy, print, scan, optional: fax
Print technology	Laser b/w
Original format	max A3 from platen glass
Copy/print speed	CD 1242: max 42 A4 pages/min and max 23 A3 pages/min CD 1252: max 52 A4 pages/min and max 26 A3 pages/min
1st copy/warm-up time	3.9 seconds*, 30 seconds
Copy resolution	600 x 600 dpi
Greyscales	256
Paper feed	2 x 500 sheet universal cassettes (A3-A5R), 200 sheet multi-bypass (A3-A6R)
Paper weights	Universal cassette 60-105 g/m ² , multi-bypass 45-200 g/m ² , duplex 60-80 g/m ²
Paper output	250 sheet A4
System memory	2,048 MB RAM, 160 GB HDD**
Continuous copying	1-999 copies
Zoom	25%-400% in steps of 1%
Functions	Adjustable touch screen, duplex, multi-tasking controller, printing from/scanning to USB stick, job reservation, N-up, booklet mode, 1,000 management codes, etc.

	DIMENSIONS/WEIGHT
Dimensions	745 x 599 x 646 mm (H x W x D)
Weight	approx. 85 kg

	ENVIRONMENT
Mains voltage	220/240 V, 50/60 Hz
Power consumption	approx. 1,060 W in operation, approx. 240 W in stand-by mode, approx. 21 W in sleep mode
Noise level	approx. 69 dB(A) in operation, approx. 52 dB(A) in stand-by mode (ISO 7779/9296)
Safety	GS/TÜV, CE

	PRINT SYSTEM
Type	Integrated within the system
Print format	A3-A6R
Print resolution	600 x 600 dpi
Processor	PowerPC 750FL/600 MHz
Interfaces	USB 2.0, 10/100 BaseTX, USB host (2), CF slot
Network protocols	TCP/IP, IPX/SPX, Net BEUI, EtherTalk
Operating systems	Windows 2000, XP, Vista, Windows 7, Server 2003/2008, Novell NetWare, Linux, Mac ex OS 10.2
Emulations	PCL6, KPD3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850
Functions	PDF/XPS direct printing, printing of e-mails, barcode printing

*Depending on operating status.
**For copy, print, scan and fax.

	SCAN SYSTEM
Scan type	CCD colour and b/w
Scan format	max A3
Scan speed	b/w: max 75/100 A4 pages/min (simplex/duplex) with 300 dpi, colour: max 50/60 A4 pages/min (simplex/duplex) with 300 dpi (with DP-760)
Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi
Scan mode	Photo, text, photo/text, OCR
File types	TIFF, PDF, JPEG, XPS
Interface	10/100 BaseTX
Network protocol	TCP/IP
Operating systems	Windows 2000, XP, Vista, Windows 7, Server 2003/2008
Functions	Scan to SMB, scan to e-mail, scan to FTP, TWAIN scan (Windows 2000, XP, Vista, Server 2003/2008), WIA scan (Windows Vista, Windows 7, Server 2008), scan to USB, SMTP authentication, LDAP, PDF compression and encryption

	OPTIONAL FAX SYSTEM (S)
Compatibility	Super G3
Original format	max A3
Modem speed	33.6 kbps
Transmission speed	3 seconds or less using JBIG
Compression method	JBIG, MMR, MR, MH
Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi), 600 x 600 dpi
Fax memory	12 MB (max 120 MB)
Abbreviated dial	2,000 numbers
One touch dial	100 numbers
Group dial	500 numbers
Operating systems	Windows 2000, XP, Vista, Windows 7, Server 2003/2008
Functions	Network fax driver, automatic redialling, delayed transmission, max 2 fax kits for simultaneous transmission and reception

OPTIONS

Original feeder	DP-750 document processor with automatic reverse function (A3-A5R, capacity: 100 sheet, paper weight 45-160 g/m ²), DP-760 document processor with simultaneous duplex scanning (A3-A5R, capacity: 100 sheet, paper weight 45-160 g/m ²)
Platen cover	Platen cover type E (if document processor is not installed)
Finisher	DF-720 (B) internal finisher (capacity: 500 sheet A4, stapling max 30 sheet A4), DF-780 (B) (capacity: 1,000 sheet A4, stapling max 50 sheet A4), DF-760 (B) (capacity: 3,000 sheet A4, stapling max 50 sheet A4), PH-5C hole punch unit for DF-760 (B), BF-720 brochure module for DF-760 (B) (max 16 sheet saddle stitching and folding A3/A4/B4), MT-720 (B) multi tray for DF-760 (B)
Job separator	JS-700 (B) (capacity: 100 sheet A4)
Paper feed	PF-720 (B) (2 x 500 sheet universal cassettes (A3-A5R)), PF-760 (B) (3,000 sheet large capacity cassette (A4/B5))
Other options	Data security kit (E), internet fax kit (A), printed document guard kit (A), DT-710 document tray, cabinet no. 56

SynControl centrally controls and synchronises all functions (copying, printing, scanning and faxing) and enables the parallel processing of data.

The CD 1242 and the CD 1252 are manufactured in accordance with the requirements of the ENERGY STAR Program. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual.

Specifications subject to change without notice.

Image shows machine with optional accessories.

Your UTAX dealer

01/2010

Following in-depth analysis of all output systems used in the company, with our **UTAX DOCUMENT CONSULTING** sales concept we create an offering precisely tailored to the customer's needs. Using the very **latest UTAX digital systems** in combination with **practical software solutions** from the DMS areas of **archiving, form printing and accounting**, the entire **output and document management** becomes extremely efficient and **costs are reduced**.

www.utax.com
UTAX and the UTAX logo are registered trademarks of UTAX GmbH. All other brand names referred to are registered trademarks of the respective manufacturers.

